



Distributed by Sunlux




Product Features


- Universal input voltage / Full range: 198~528Vac IP66
- Constant Power Design
- DMX-RDM control optional, support RDM control mode & controller address setting
- Support flashing function with with maximun of 6 flashes per second
- Non-Isolated class I Driver
- Efficiency up to 96.5%
- DMX&DALI-2 Control interface
- dim-to-off, no Glow after dim-to-off
- Max remote distance 300 meters
- Surge protection: 10KV line-line, 10KV line-earth @2Ω. Mutiple protection: SCP, OVP, OTP
- 5 year Warranty
- Best use in, Stadium Lighting, Area and Flood Lighting, High-bay Lighting etc.



Model N°	Max Output Power (W)	Output Volt. (Vdc)	Input Voltage Range (Vac)	Full Power Output Current Range (A)	Default Current (A)	Typical Efficiency	Power Factor
S6-880Y440	880W	190-440V	198-528Vac	2.0~3.60A	2.5A	96.5%	0.96

Physical

Size: mm









Wire Ports

V1+, V3+ cannot be connected together



DALI Wiring Connection



DMX Wiring Connection

Cautions

1. After the wiring is connected according to the datasheet, ensure that the gland is effectively locked to prevent water from damaging the driver.
2. When closing the electrical cover after wiring, ensure that the four fixing screws effectively tightened to prevent water from damaging the driver.

Specification

General Specifications

Parameter	Description			Notes
	Min.	Typ.	Max.	
Efficiency @220Vac	94.5%	96%	—	Measured at full load and 25°C - ambient temperature
Efficiency @220Vac	93.5%	95%	—	
Efficiency @277Vac	95.0%	96.5%	—	
Efficiency @277Vac	94%	95.5%	—	
Efficiency @347Vac	95%	96.5%	—	
Efficiency @347Vac	94%	95.5%	—	
Efficiency @480Vac	95%	96.5%	—	
Efficiency @480Vac	94%	95.5%	—	
Mean Time Between Failure	—	200Khours	—	25°C +/- 10°C ambient temperature, 220Vac, 80% load
Lifetime	—	50Khours	—	Ta=45°C, Tc=70°C, 220Vac & 100% load
Ambient Temperature Ta	-40°C	—	+50°C	
Operating Tc for Safety Tc_s	-40°C	—	+85°C	
Operating Tc for Warranty Tc_w	-40°C	—	+70°C	5 years warranty case temperature. Humidity: 10-80% RH No condensation
Storage Temperature Ta	-40°C	—	+85°C	
Altitude	-60m	—	4000m	
Input Under Voltage Protection	150Vac	170Vac	190Vac	
External NTC (R1)	—	18K Ohm (Set by Software)	—	When the R-NTC is reduced to R1, the external thermal protection is triggered and the output current gradually decreases
External NTC (R1)	—	9.1K Ohm (Set by Software)	—	When the R-NTC is reduced to R2, the output current is reduced to the programmed protection current value
External NTC (Protection Circuit)	10%I _o set	60%I _o set	100%I _o set	10%I _o set > I _o min (Default setting 60%)
External NTC (Protection Circuit)	I _o min	60%I _o set	100%I _o set	10%I _o set ≤ I _o min (Default setting 60%)
Over Temperature Protection Tc	—	90°C	95°C	Tc; 220Vac & 100% load
Short Circuit Protection	—	—	—	Self - recovery
Dimensions (L*W*H)	15.74" * 5.90" * 3.18" (Inches)			
Net Weight	9.59 +/- 0.22 Lbs			

Safety Parameter	CCC	CE/ENE/SAA	UL	Notes
Dielectric Strength (Input - Ground)	2100Vac	2100Vac	2100Vac	60S, Current not exceeding 10mA
Dielectric Strength (Output - Ground)	2100Vac	2100Vac	2100Vac	
Dielectric Strength (Input - Dim)	4870Vac	4150Vac	2100Vac	
Grounding Resistance	0.1Ω (Max)			25°C +/- 10°C Ambient Temp. pass 25A Current, 60S
Insulation Resistance	10MΩ (Min)			Input-PE, Output-PE, 500Vdc/60s/25°C/70%RH

Output Specifications

Parameter	Description			Notes
	Min.	Typ.	Max.	
Output Voltage Range	190Vdc	—	440Vdc	The full power cannot be lower than 300Vdc
Open Circuit Voltage	—	—	530Vdc	The open circuit protection is locked, and the AC needs to be powered on again
Open Current Range	5%I _{set}	—	100% I _{set}	Adjustable Output Current with Programmer
Output Current Range	2.0A	—	3.60A	
Current Accuracy	-3%	—	+3	
Total Output Current Ripple (Pk-Pk)	—	0.5%	1.0%	20MHz BW, full load & LED load, the ripple would be tiny different under different LED load.
Startup Overshoot Current	—	—	—	No Overshoot
Line Regulation	-2%	—	+2%	25°C +/- 10°C ambient temperature input voltage changes from 220Vac to 400Vac.
Load Regulation	-1%	—	+1%	25°C +/- 10°C ambient temperature input voltage 400Vac. load changes from 80% to 100%
Turn-on Delay Time	—	—	1.5s	220~400Vac & 100% load, load is LED

Input Specifications

Parameter	Description			Notes
	Min.	Typ.	Max.	
Input Voltage Typ	220Vac	230/277/347/400/400Vac	480Vac	
Input Frequency AC	47Hz	50/60Hz	63Hz	
Input Voltage Range	198Vac	–	528Vac	Refer to output power vs input curve
Max Input current	–	–	4.5A	220Vac&Full Load
Max Input Power	–	–	950W	220Vac&Full Load
Protective Conductor Current	–	–	3.5mA	220-480Vac/60Hz
Leakage	–	–	0.75MIU	UL8750
Inrush Current	–	0.8A(2)S	1.0A2S	480Vac, full load, 50%~50% peak Pulse duration
Inrush Current	–	30A	35A	480Vac&Full load, Cold Start
Stand by Power Consumption	–	–	0.5W	230Vac&50Hz
Power Factor (PF)	0.97	0.99	–	220-277Vac, 50/60Hz, 100% Load
Power Factor (PF)	0.94	0.96	–	400Vac, 50/60Hz, 100% Load
Power Factor (PF)	0.92	0.94	–	480Vac, 50Hz, 100% Load
Power Factor (PF)	0.95	0.97	–	220-277Vac, 50/60Hz 80% Load
Power Factor (PF)	0.93	0.95	–	347Vac, 50/60Hz, 80% Load
Power Factor (PF)	0.92	0.94	–	480Vac, 50Hz, 80% Load
Total Harmonic Distorsion (THD)	–	6%	15%	220-480Vac, 50/60Hz, 100% Load
Total Harmonic Distorsion (THD)	–	10%	20%	220-480Vac, 50/60Hz, 80-100% Load


DMX Dimming

Parameter	Description			Notes
	Min.	Typ.	Max.	
DMX+ to DMX-	-6V	–	6V	
DMX+ to Chassis	22M Ohm	–	–	at 42Vdc
DMX- to Chassis	22M Ohm	–	–	at 42Vdc
Logic 0 input	–	–	-0.2V	DMX+ to DMX-
Logic 1 Input	0.2V	–	–	DMX+ to DMX-
Communication Baud Rate	–	250K bps	–	
Dimming Output Range	5% Iomax	–	100% Loset	
Dimming Value with turn off	–	–	1	5% Iomax
Dimming Value with turn on	–	–	0	
Flashing times per second	–	–	6	0% - 100% Iset


DALI-2 Dimming

Parameter	Description			Notes
	Min.	Typ.	Max.	
High Voltage Level	9.5V	16V	22.5V	
Lower Voltage Level	-6.5V	0V	6.5V	Return terminal is "DA–"
Dimming Output Current Range	5% Imax	–	100% Imax	Imax = 3.6A
Sink Current	–	–	2.0mA	
Timer Dimming	–	–	–	Traditional, Self-adaption
Output Lumen Compensation	–	–	–	Constant lumen output function


Inrush Current




Output Voltage Vs. Output Current




Output Power vs. Input Voltage




Efficiency vs Load (Io=2.0A)




Efficiency vs Load (Io=3.6A)




PF vs Load




THD vs Load




Output Power vs Load Ambient Temperature



Lifetimes vs Case Temperature



DMX Dimming Curve



DALI-2 Dimming Curve

